

Categories

- Water Feature
 - > Pond Pumps
 - > Pond Skimmers
 - > Pond Liners
 - > Waterfall Weirs
 - > Disappearing Falls
 - > Water Treatments
 - > Pond Lighting
 - > Pond Construction

Sump and Sewage Pressure Boost Dewatering

Search

Login

Email Address:

Password:
You will be prompted to enter your password on the next page

Create an account
Forgot Password?

Manufacturers

Select ...

Home > Water Feature > Pond Pumps

Shinmaywa 65CVC41.5S-2



Features

- 3" NPT Discharge
- 2" Solids handling
- Vortex impeller for superior solids handling capability
- Air filled Class E Insulated heavy duty motor operates cooler with higher efficiencies
- Double mechanical shaft seals made of silicon carbide and upper of Carbon Ceramic. Seals operate in an oil bath to provide longer service life and lower maintenance
- Capacitor and power cord connections are isolated from motor housing and easily accessible for field maintenance
- 32' Power cable length
- Stainless Steel non corrosive hardware
- Auto cut thermal overload protects the pump from over-current and over-temperature.

Construction

Flange Connection	3" NPT
Housing	Cast Iron
Impeller	Cast Iron
Impeller Type	Vortex
Volute	Cast Iron
Mechanical Seals	Double CC/SC
Power Cord	32 ft, PVC
Fasteners	304 SS
Shaft	420 SS
Motor RPM	1800
Bearings	Double Ball Bearing
Capacitor	35 MF 400V
Insulation Class	E

Specifications and Performance

Model	HP	Volt
65CVC41.5S-2	2	230



ShinMaywa are the continuous duty m...

- 3" Female
- Single Phase
- Vortex impeller
- Air filled Class E Insulated heavy duty motor operates cooler with higher efficiencies
- Double mechanical shaft seals made of silicon carbide and upper of Carbon Ceramic. Seals operate in an oil bath providing longer service life and lower maintenance
- Capacitor and power cord connections are isolated from motor housing and easily accessible for field maintenance
- 32' Cable length
- Stainless Steel non corrosive hardware
- Auto cut thermal overload protects the pump from over current and over temperature
- 2 Year Warranty

Head (ft)	Flow (GPH)
5	16,500
10	14,400
15	12,000
20	10,800
38'	Shut off

Features

- 3" NPT Discharge
- 2" Solids handling
- Vortex impeller for superior solids handling capability
- Air filled Class E Insulated heavy duty motor operates cooler with higher efficiencies
- Double mechanical shaft seals with the lower made of silicon carbide and upper of Carbon Ceramic. Seals operate in an oil bath to provide longer service life and lower maintenance
- Capacitor and power cord connections are isolated from motor housing and easily accessible for field maintenance
- 32' Power cable length
- Stainless Steel non corrosive hardware
- Auto cut thermal overload protects the pump from over-current and over-temperature.



Construction

Flange Connection	3" NPT
Housing	Cast Iron
Impeller	Cast Iron
Impeller Type	Vortex
Volute	Cast Iron
Mechanical Seals	Double CC/SC
Power Cord	32 ft, PVC
Fasteners	304 SS
Shaft	420 SS
Motor RPM	1800
Bearings	Double Ball Bearing
Capacitor	35 MF 400V
Insulation Class	E

Specifications and Performance

Model	HP	Volts	Amps	GPM / GPH @ ft of head					Max	
				Flow	5'	10'	15'	20'		25'
65CVC41.5S-2	2	230	10	GPM	265	230	195	170	135	37'
				GPH	15,900	13,800	11,700	10,200	8,100	

www.shinmaywasales.com